

---

---

# COMP1511 - Programming Fundamentals

— Term 2, 2019 - Lecture 10 —

---

---

# What did we learn yesterday?

## Assignment 1 - CS Paint

- Assessment and some details

## Functions and Libraries

- Including other C Libraries

## Professionalism

- What's more important than just coding?

# What are we covering today?

## Characters and Strings

- A new variable type!
- Using letters and words in C

## Halfway point of COMP1511

- Let's make a program that uses everything we've learnt so far

# Characters

## We've only used ints and doubles so far

- We have a new type called **char**
- Characters are what we think of as letters, like 'a', 'b', 'c' etc
- They can also represent numbers, like '0', '1', '2' etc
- They are actually **8 bit** integers!
- We use them as characters, but they're actually encoded numbers
- ASCII (American Standard Code for Information Interchange)
- We will not be using **char** for individual characters, but we will in arrays

# ASCII and Characters as numbers

**We make use of ASCII, but we don't need to know it**

- ASCII specifically uses values 0-127 and encodes:
  - Upper and Lower case English letters
  - Digits 0-9
  - Punctuation symbols
  - Space and Newline
  - And more . . .
- It's not necessary to memorise ASCII, rather it's important to remember that characters can be treated like numbers sometimes

# Characters in code

```
#include <stdio.h>

int main (void) {
    // we're using an int to represent a single character
    int character;
    // we can assign a character value using single quotes
    character = 'a';
    // This int representing a character can be used as either
    // a character or a number
    printf("The letter %c has the ASCII value %d.\n", character,
character);
    return 0;
}
```

Note the use of %c in the printf will format the variable as a character

# Helpful Functions

`getchar()` is a function that will read a character from input

- Reads a byte from standard input
- Usually returns an int between 0 and 255 (ASCII code of the byte it read)
- Will sometimes return a -1 for EOF (which is why we use an int, not a char)
- Sometimes `getchar` won't get its input until a newline is entered

`putchar()` is a function that will write a character to output

- Will act very similarly to `printf("%c", character);`

# Use of getchar() and putchar()

```
// using getchar() to read a single character from input
int inputChar;
printf("Please enter a character: ");
inputChar = getchar();
printf("The input %c has the ASCII value %d.\n", inputChar, inputChar);

// using putchar() to write a single character to output
putchar(inputChar);
```



# Invisible Characters

There are other ASCII codes for “characters” that can’t be seen

- Newline(`\n`) is a character
- Space is a character
- There’s also a special character called EOF (End of File) that signifies that there’s no more input
- EOF has been `#defined` in `stdio.h`, so we use it like a constant
- We can signify the end of input in a Linux terminal by using Ctrl-D

# Working with multiple characters

We can read in multiple characters (including space and newline)

This code is worth trying out . . . you get to see that space and newline have ASCII codes!

```
// reading multiple characters in a loop
int readChar;
readChar = getchar();
while (readChar != EOF) {
    printf("I read character: %c, with ASCII code: %d.\n",
           readChar, readChar);
    readChar = getchar();
}
```

# More Character Functions

`<ctype.h>` is a useful library that works with characters

- `int isalpha(int c)` will say if the character is a letter
- `int isdigit(int c)` will say if it is a numeral
- `int islower(int c)` will say if a character is a lower case letter
- `int toUpper(int c)` will convert a character to upper case
- There are more! Look up `ctype.h` references or `man` pages for more information

# Strings

When we have multiple characters together, we call it a string


- Strings in C are arrays of `char` variables containing ASCII code
- Strings are basically words, while chars are letters
- Strings have a helping element at the end, a `'\0'`
- It's often called the null terminator and it is an invisible character
- This helps us know if we're at the end of the string

# Strings in Code

Strings are arrays of type `char`, but they have a convenient shorthand

```
// a string is an array of characters
char word1[] = {'h', 'e', 'l', 'l', 'o'};
// but we also have a convenient shorthand
// that feels more like words
char word2[] = "hello";
```

Both of these strings will be created with 6 elements. The letters `h`, `e`, `l`, `l`, `o` and the null terminator `\0`



# Reading and writing strings

`fgets(array[], length, stream)` is a useful function for reading strings

- It will take up to **length** number of characters
- They will be written into the **array**
- The characters will be taken from a stream
- Our most commonly used stream is called **stdin**, “standard input”
  
- **stdin** is our user typing input into the terminal
- We also have **stdout** which is our stream to write to the terminal

# Reading and writing strings in code

```
// reading and writing lines of text
char line[MAX_LINE_LENGTH];
while (fgets(line, MAX_LINE_LENGTH, stdin) != NULL) {
    fputs(line, stdout);
}
```

- `fputs(array, stream)` works very similarly to `printf`
- It will output the string stored in the array to the standard output

# Helpful Functions in the String Library

`<string.h>` has access to some very useful functions

Note that `char* s` is equivalent to `char s[]`

- `int strlen(char* s)` - return the length of the string (not including `\0`)
- `strcpy` and `strncpy` - copy the contents of one string into another
- `strcat` and `strncat` - attach one string to the end of another
- `strcmp` and variations - compare two strings
- `strchr` and `strrchr` - find the first or last occurrence of a character
- And more ...



# Break Time

**Learning something new is better than being good at something!**

Remember . . . as nice as high marks are, they're not the same as long term fulfilment

*"I don't care who you are, where you're from, what you've done . . . as long as you love C." - The Backstreet Boys*



# Whoaaaah We're Halfway There ...

We're going to use a bit of everything we've seen so far in COMP1511

**This program is a word game**

- It will read in a string from the user
- It will then read in another string from the user and tell us how many of the letters from the second appear in the first
- This will use if, while, arrays (of characters) and functions

# Where will we start?

## A simple version to begin with

- Let's read in a line of characters
- Then read in a single character and see whether it's in the line or not

# Read in a line of characters (a string)

We can use a nice library function here

- `fgets()` will grab an entire line from standard input
- We can set up a maximum line size as well

```
#define MAX_LINE_LENGTH 100

int main(void) {
    char line[MAX_LINE_LENGTH];
    fgets(line, MAX_LINE_LENGTH, stdin);
}
```

# Read in a single character

Starting simple, we can take a character as input

- `getchar()` will read a single character from standard input
- Remember that we'll be using ints as our types for characters
- Here we can loop and continually get characters until input ends

```
int inputChar;  
inputChar = getchar();  
while (inputChar != EOF) {  
    inputChar = getchar();  
}
```

# A Function to find a character in a string

Loop through the string, testing for a character

- We've done this kind of loop before with other types!

```
int testChar(char c, char line[MAX_LINE_LENGTH]) {
    int charCount = 0;
    int i = 0;
    while (i < MAX_LINE_LENGTH && line[i] != '\0') {
        if (line[i] == c) {
            charCount++;
        }
        i++;
    }
    return charCount;
}
```

# Simple functionality ... how well is it working?

## What tests should we run at this point?

- Look for syntax errors using our compiler (dcc)
- Look for logical errors by testing with different inputs

## We might need to add in some extra outputs

- If we're getting strange behaviour, we can confirm our guesses
- We might learn more about what's going on in our program

# What are these extra characters?

Maybe we need to check what those characters are

- Some print statements can help here

```
int inputChar;
inputChar = getchar();
while (inputChar != EOF) {
    printf("Main loop running, readChar is %c.\n", inputChar);
    printf("%d\n", testChar(inputChar, line));
    inputChar = getchar();
}
```



# Dealing with little issues

**We're reading newlines (`\n`) as characters!**

- Let's remove the newlines from both our line and our inputs
- We'll use a library function, `strlen()` to find the end of a string
- To use `strlen()`, we will need the `string.h` library, which we will include
- We'll then replace the `\n` with `\0` which will end the string early

# Removing newlines

Removing a `\n` at the end of a string:

```
int main(void) {  
    char line[MAX_LINE_LENGTH];  
    fgets(line, MAX_LINE_LENGTH, stdin);  
    int length = strlen(input);  
    input[length - 1] = '\0';  
}
```

Ignoring the `\n` while reading input:

```
inputChar = getchar();  
if (inputChar == '\n') {  
    inputChar = getchar();  
}
```

# Expanding on the functionality

## Our first attempt just checked for single letters

- Now we expand to words!
- Read in another word
- Check every letter in the word for whether it appears in the phrase
- Then report back how many letters matched

## Some good reasons to use functions!

- Reading in words is now duplicated
- We can reuse our testChar() function to see if letters match

# A function to read a line

This function also removes the `\n` that `fgets` will give us

```
void readString(char input[MAX_LINE_LENGTH]) {  
    fgets(input, MAX_LINE_LENGTH, stdin);  
    int length = strlen(input);  
    input[length - 1] = '\0';  
}
```

# A function to count letters

Counts how many letters from one string appear in the other

This function also uses another function!

```
int numLetterMatches(char word[MAX_LINE_LENGTH], char line[MAX_LINE_LENGTH]) {
    int i = 0;
    int matchCount = 0;
    while (i < MAX_LINE_LENGTH && word[i] != '\0') {
        if (testChar(word[i], line)) {
            matchCount++;
        }
        i++;
    }
    return matchCount;
}
```

# A simple word game

**What coding concepts have we used there that might come in handy?**

- Characters and Strings (note that we'll never need the ASCII table to work with characters)
- Using libraries and provided functions
- Loops on strings (using the Null Terminator `\0`)
- Writing multiple functions and using functions within functions
- A lot of our basic C concepts like `if`, `while` and array indexing

# What did we learn today?

## Characters and Strings

- Using letters and words in C
- Using functions from libraries

## Coding using everything we've learnt so far

- A single program that tries to use most concepts we've covered in the first half of this course