Introduction to ROS

COMP3431/9434 Robot Software Architectures

Robot Software Architecture

- A robot's software has to control a lot of things:
 - 2D/3D Cameras, LIDAR, Microphones, etc
 - Drive motors, Arm motors
 - Vision, Mapping, Navigation
 - Task Planning, Motion Planning
 - Speech and Natural Language Processing

•

Robot Software Architecture

- Component-based software design put each function in its own module
- Need a communication mechanism between components

ROS (Robot Operating System)

- Open-source
- NOT an operating system:
 - Peer-to-peer comms for distributed processes (*nodes*).
 - Library of drivers, filters (e.g., mapping), behaviours (e.g., navigation)
- Not real-time
- OS agnostic (in theory, but only really works on Ubuntu)
- Language agnostic:

– APIs for Python and C++ and other languages

ROS Basics

- ROS Nodes registration at process startup
- Two models of comms between nodes:
 - ROS Topics: Publisher-subscriber (many-to-many).



*Commonly: one publisher and many subscribers

ROS Basics

- ROS Nodes registration at process startup.
- Two models of comms between nodes:
 - ROS Topics: Publisher-subscriber (many-to-many).
 - ROS Services: remote procedure call (one-to-one).



ROS Basics

- ROS Nodes registration at process startup
- Two models of comms between nodes:
 - ROS Topics: Publisher-subscriber (many-to-many)
 - -ROS Services: remote procedure call (one-to-one)
- ROS ActionLib
 - Services with incremental feedback
 - built using ROS topics

Messages

- Topics and services use a well-defined message format:
 - Primitive types (e.g., int8, bool, string, etc).
 - User-defined types (e.g., geometry_msgs/Point, sensor_msgs/LaserScan).
 - ROS takes care of generating language bindings (e.g., C++, Python).

geometry_msgs/Point

float64 x float64 y float64 z

- TCP/IP model nodes can run on same or different computers.
- ROS *master* provides directory services.
- Scenario: *laser* node publishes and *mapping* node subscribes.



- TCP/IP model nodes can run on same or different computers
- ROS *master* provides directory services
- Scenario: *laser* node publishes and *mapping* node subscribes



- TCP/IP model nodes can run on same or different computers.
- ROS *master* provides directory services.
- Scenario: *laser* node publishes and *mapping* node subscribes.

Mapping node registers with master that it is subscribing to the topic name.



- TCP/IP model nodes can run on same or different computers.
- ROS *master* provides directory services.
- Scenario: *laser* node publishes and *mapping* node subscribes.





- TCP/IP model nodes can run on same or different computers.
- ROS *master* provides directory services.
- Scenario: *laser* node publishes and *mapping* node subscribes.

Mapping node initiates direct connection with laser node.



- TCP/IP model nodes can run on same or different computers.
- ROS *master* provides directory services.
- Scenario: *laser* node publishes and *mapping* node subscribes.

Laser node publishes and mapping node receives laser scan messages.



- TCP/IP model nodes can run on same or different computers.
- ROS *master* provides directory services.
- Scenario: *laser* node publishes and *mapping* node subscribes.

- NOTE: In reality a bit more complicated:
 - Laser node does not have to register first
 - Multiple publishers and multiple subscribers
 - But same outcome peer-to-peer data transfer



Node/Topic Example



Nodes in a Distributed System

- Nodes can be on different computers.
- Requires some care:
 - Turn off local firewalls
 - Environment variables to specify addresses of nodes and master:
 - ROS_MASTER_URI location of the master.
 - ROS_HOSTNAME node will register with master using this value.

– Safest to use IP addresses (not hostnames).

export ROS_MASTER_URI=http://192.168.1.2:11311
export ROS_HOSTNAME=192.168.1.5

IP Address of robot

Packages – Flexible Structure

- Dependencies to other packages.
- Custom *messages* and *service* definitions.
- Specify nodes O or more.
- Libraries export for use by other packages.

Catkin Workspaces

- Used for compiling and running a catkin system.
- Workspace layout:

```
catkin_ws/
    src/my_package/ - individual packages placed here
    build/
    devel/ - install location for development files
```

- Catkin tools are run within workspace directory.
- To compile your workspace:
 - \$ cd catkin_ws
 \$ catkin_make

Catkin Packages

• *Catkin* – the ROS build system:

- Combines *CMake* (popular C++ build tool) and some Python components.
- User-built components are organised in *packages*.
- A typical package:

```
mypackage/
```

CMakeLists.txt package.xml src/ include/ scripts/ setup.py

- CMakeLists.txt CMake building
 - dependencies between packages
 - source directory: C++/Python/Java/etc
 - typical for C++ headers
 - typical for Python
 - python installation file
- Use the Catkin tools: catkin_create_pkg my_package depend1 ...

Names and Namespaces - Warning

- ROS uses namespaces in different contexts.
- Positive: easy to avoid name clashes.
- Negative: can create confusion.
- Do not confuse namespace usage in:
 - Node names.
 - Topic names.
 - Frames of reference to be discussed later.
- Node name "/mynode/laser" is different from frame "/mynode/laser".

Sample Code

- Create a simple publisher and subscriber (both in Python and C++).
- Simple example track location of a robot (ignoring orientation):
 - Publisher publish a geometry_msgs/Point.
 - Subscriber can then use data (eg., to locate robot on map).

Laboratories

- Work through the ROS tutorials.
 - -<u>http://wiki.ros.org/ROS/Tutorials</u>.
 - -<u>http://emanual.robotis.com/docs/en/platform/turtlebot3/overview</u>
- First assignment:
 - due week 4.
 - Turtlebot3 navigation task.
 - -Get as soon as you can!