

Answer Set Programming¹

Abdallah Saffidine

COMP4418

¹Slides designed by Christoph Schwering

Non-Monotonic Reasoning



Non-Monotonic Reasoning



$\forall x (\text{Car}(x) \rightarrow \neg \text{Entry}(x))$

Non-Monotonic Reasoning



$\forall x (\text{Car}(x) \rightarrow \neg \text{Entry}(x))$

$\forall x (\text{Car}(x) \wedge \text{Auth}(x) \rightarrow \text{Entry}(x))$

Non-Monotonic Reasoning



$$\left. \begin{array}{l} \forall x (\text{Car}(x) \rightarrow \neg \text{Entry}(x)) \\ \forall x (\text{Car}(x) \wedge \text{Auth}(x) \rightarrow \text{Entry}(x)) \end{array} \right\} \models \text{Car}(C) \wedge \text{Auth}(C) \rightarrow \neg \text{Entry}(C)$$

ASP at a Glance

- ASP = Answer Set Programming
 - ▶ ASP \neq Microsoft's Active Server Pages
- ASP belongs to logic programming
 - ▶ Like Prolog: $Head \leftarrow Body$ or $Head :- Body.$
 - ▶ Like Prolog: negation as failure
 - ▶ Unlike Prolog: $Head$ may be empty \Rightarrow constraints
- Declarative programming
 - ▶ Unlike Prolog: no procedural control
 - ▶ Order has no impact on semantics
- ASP programs compute *models*
 - ▶ Unlike Prolog: not query-oriented, no resolution
 - ▶ Unlike Prolog: not Turing-complete
 - ▶ Tool for problems in NP and NP^{NP}

Motivation for ASP and this Lecture

- Very useful in practice!
 - ▶ Declarative problem solving
 - ▶ Very fast to write
 - ▶ Very fast to run
 - ▶ Few experts


- Interesting case study
 - ▶ Small, simple core language
 - ▶ Great expressivity by reduction to core language

- Knowing the theory is essential

Example: Graph Colouring

Definition: graph colouring problem


Input: graph with vertices V and edges $E \subseteq V \times V$, set of colors C .
Is there a mapping $m : V \rightarrow C$ with $m(x) \neq m(y)$ for all $(x,y) \in E$?



Example: Graph Colouring

Definition: graph colouring problem

Input: graph with vertices V and edges $E \subseteq V \times V$, set of colors C .
Is there a mapping $m : V \rightarrow C$ with $m(x) \neq m(y)$ for all $(x,y) \in E$?



Example: Graph Colouring

Definition: graph colouring problem


Input: graph with vertices V and edges $E \subseteq V \times V$, set of colors C .
Is there a mapping $m : V \rightarrow C$ with $m(x) \neq m(y)$ for all $(x, y) \in E$?

- Graph Colouring is NP-complete
 - ▶ NP: guess solution, verify in polynomial time
 - ▶ NP-complete: among hardest in NP
- Many applications:
 - ▶ Mapping (neighbouring countries to different colors)
 - ▶ Compilers (register allocation)
 - ▶ Scheduling (e.g., conflicting jobs to different time slots)
 - ▶ Allocation problems, Sudoku, ...

Example: Graph Colouring

Definition: graph colouring problem

Input: graph with vertices V and edges $E \subseteq V \times V$, set of colors C .
Is there a mapping $m : V \rightarrow C$ with $m(x) \neq m(y)$ for all $(x,y) \in E$?



$c(r) . c(g) . c(b) .$

$v(1) . \dots v(6) .$

$e(1, 2) . e(1, 3) . e(1, 4) .$

$e(2, 4) . e(2, 5) . e(2, 6) .$

$e(3, 1) . e(3, 4) . e(3, 5) .$

$e(4, 1) . e(4, 2) .$


$e(5, 3) . e(5, 4) . e(5, 6) .$

$e(6, 2) . e(6, 3) . e(6, 5) .$

Example: Graph Colouring

Definition: graph colouring problem

Input: graph with vertices V and edges $E \subseteq V \times V$, set of colors C .
Is there a mapping $m : V \rightarrow C$ with $m(x) \neq m(y)$ for all $(x,y) \in E$?



$c(r) . c(g) . c(b) .$

$v(1) . \dots v(6) .$

$e(1, 2) . e(1, 3) . e(1, 4) .$

$e(2, 4) . e(2, 5) . e(2, 6) .$

$e(3, 1) . e(3, 4) . e(3, 5) .$

$e(4, 1) . e(4, 2) .$

$e(5, 3) . e(5, 4) . e(5, 6) .$


$e(6, 2) . e(6, 3) . e(6, 5) .$

$1 \{m(X, C) : c(C)\} 1 :- v(X) . \quad \text{guess mapping } m$
 $:- e(X, Y), m(X, C), m(Y, C) . \quad \text{verify } m(X) \neq m(Y)$

Example: Graph Colouring

Definition: graph colouring problem

Input: graph with vertices V and edges $E \subseteq V \times V$, set of colors C .
Is there a mapping $m : V \rightarrow C$ with $m(x) \neq m(y)$ for all $(x,y) \in E$?



$c(r)$. $c(g)$. $c(b)$.

$v(1)$ $v(6)$.

$e(1, 2)$. $e(1, 3)$. $e(1, 4)$.

$e(2, 4)$. $e(2, 5)$. $e(2, 6)$.

$e(3, 1)$. $e(3, 4)$. $e(3, 5)$.

$e(4, 1)$. $e(4, 2)$.

$e(5, 3)$. $e(5, 4)$. $e(5, 6)$.

$e(6, 2)$. $e(6, 3)$. $e(6, 5)$.

$1 \{m(X, C) : c(C)\} 1 :- v(X)$. guess mapping m
 $:- e(X, Y), m(X, C), m(Y, C)$. verify $m(X) \neq m(Y)$

Applications of ASP

- Automated product configuration
 - Linux package manager
 - Decision-support system for space shuttle
 - Bioinformatics (diagnosis, inconsistency detection)
 - General game playing
-
- Several implementations are available
 - For this lecture: **Clingo** www.potassco.org

Overview of the Lecture

- **Semantics of ASP programs**
- Extensions of ASP programs
- Handling of variables in ASP
- ASP as modelling language

Prolog vs ASP

Consider the following logic program:

■ $a.$	$a.$
$c \leftarrow a, b.$	$c :- a, b.$
$d \leftarrow a, \text{not } b.$	$d :- a, \text{not } b.$

Prolog vs ASP

Consider the following logic program:

- a .
 $c \leftarrow a, b$.
 $d \leftarrow a, \text{not } b$.
- Prolog proves by SLD resolution:

Prolog vs ASP

Consider the following logic program:

- a .
 $c \leftarrow a, b$.
 $d \leftarrow a, \text{not } b$.
- Prolog proves by SLD resolution:
 - ▶ Proves a (for a is a fact)

Prolog vs ASP

Consider the following logic program:

■ $a.$

$c \leftarrow a, b.$

$d \leftarrow a, \text{not } b.$

■ Prolog proves by SLD resolution:

▶ Proves a (for a is a fact)

▶ Cannot prove b (for b is in no head)

Prolog vs ASP

Consider the following logic program:

■ $a.$

$c \leftarrow a, b.$

$d \leftarrow a, \text{not } b.$

■ Prolog proves by SLD resolution:

▶ Proves a (for a is a fact)

▶ Cannot prove b (for b is in no head)

▶ Cannot prove c (for cannot prove b)

Prolog vs ASP

Consider the following logic program:

■ $a.$

$c \leftarrow a, b.$

$d \leftarrow a, \text{not } b.$

■ Prolog proves by SLD resolution:

▶ Proves a (for a is a fact)

▶ Cannot prove b (for b is in no head)

▶ Cannot prove c (for cannot prove b)

▶ Proves d (for prove a but not b)

Algorithm defines what Prolog does

Prolog vs ASP

Consider the following logic program:

■ $a.$

$c \leftarrow a, b.$

$d \leftarrow a, \text{not } b.$

■ Prolog proves by SLD resolution:

▶ Proves a (for a is a fact)

▶ Cannot prove b (for b is in no head)

▶ Cannot prove c (for cannot prove b)

▶ Proves d (for prove a but not b)

Algorithm defines what Prolog does

■ What is the *semantics* of this logic program?

Prolog vs ASP

Consider the following logic program:

- $a.$ a
 $c \leftarrow a, b.$ $a \wedge b \rightarrow c$
 $d \leftarrow a, \text{not } b.$ $a \wedge \neg b \rightarrow d$

■ Prolog proves by SLD resolution:

- ▶ Proves a (for a is a fact)
- ▶ Cannot prove b (for b is in no head)
- ▶ Cannot prove c (for cannot prove b)
- ▶ Proves d (for prove a but not b)

Algorithm defines what Prolog does

■ What is the *semantics* of this logic program?

- ▶ Models: $M_1 =$

a	b	c	d
1	0	0	1

 $M_2 =$

a	b	c	d
1	1	1	0

 ...

Prolog vs ASP

Consider the following logic program:

- $a.$ a
 $c \leftarrow a, b.$ $a \wedge b \rightarrow c$
 $d \leftarrow a, \text{not } b.$ $a \wedge \neg b \rightarrow d$

■ Prolog proves by SLD resolution:

- ▶ Proves a (for a is a fact)
- ▶ Cannot prove b (for b is in no head)
- ▶ Cannot prove c (for cannot prove b)
- ▶ Proves d (for prove a but not b)

Algorithm defines what Prolog does

■ What is the *semantics* of this logic program?

- ▶ Models: $M_1 = \begin{array}{|c|c|c|c|} \hline a & b & c & d \\ \hline 1 & 0 & 0 & 1 \\ \hline \end{array}$ $M_2 = \begin{array}{|c|c|c|c|} \hline a & b & c & d \\ \hline 1 & 1 & 1 & 0 \\ \hline \end{array}$...
- ▶ M_1 corresponds to Prolog, what is special about M_1 ?

Prolog vs ASP

Consider the following logic program:

- $a.$ a
 $c \leftarrow a, b.$ $a \wedge b \rightarrow c$
 $d \leftarrow a, \text{not } b.$ $a \wedge \neg b \rightarrow d$

■ Prolog proves by SLD resolution:

- ▶ Proves a (for a is a fact)
- ▶ Cannot prove b (for b is in no head)
- ▶ Cannot prove c (for cannot prove b)
- ▶ Proves d (for prove a but not b)

Algorithm defines what Prolog does

■ What is the *semantics* of this logic program?

- ▶ Models: $M_1 = \begin{array}{|c|c|c|c|} \hline a & b & c & d \\ \hline 1 & 0 & 0 & 1 \\ \hline \end{array}$ $M_2 = \begin{array}{|c|c|c|c|} \hline a & b & c & d \\ \hline 1 & 1 & 1 & 0 \\ \hline \end{array}$...

- ▶ M_1 corresponds to Prolog, what is special about M_1 ?

- ▶ M_1 is a **stable model** a.k.a. **answer set**:

M_1 only satisfies *justified* propositions

ASP gives **semantics** to **logic programming**

Intuition

The motivating guidelines behind stable model semantics are:

- A stable model satisfies all the rules of a logic program
- The reasoner shall not believe anything they are not forced to believe — the **rationality principle**

Intuition

The motivating guidelines behind stable model semantics are:

- A stable model satisfies all the rules of a logic program
- The reasoner shall not believe anything they are not forced to believe — the **rationality principle**

Next: formalisation of this intuition

For now: only ground programs, i.e., no variables

Definition: normal logic program (NLP)

A **normal logic program** P is a set of (normal) rules of the form

$$A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n.$$

where A, B_i, C_j are atomic propositions.

When $m = n = 0$, we omit the " \leftarrow " and just write A .

Definition: normal logic program (NLP)

A **normal logic program** P is a set of (normal) rules of the form

$$A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n.$$

where A, B_i, C_j are atomic propositions.

When $m = n = 0$, we omit the " \leftarrow " and just write A .

For such a rule r , we define:

- $\text{Head}(r) = \{A\}$
- $\text{Body}(r) = \{B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n\}$

In code, r is written as $A :- B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$.

Semantics: Interpretation

Definition: interpretation, satisfaction

An **interpretation** S is a set of atomic propositions.

S **satisfies** $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$ iff
 $A \in S$ or some $B_i \notin S$ or some $C_j \in S$.

In English:

- S satisfies rule iff S satisfies the head or falsifies the body
- S falsifies body iff S falsifies some B_i or satisfies some C_j

Semantics: Interpretation

Definition: interpretation, satisfaction

An **interpretation** S is a set of atomic propositions.

S **satisfies** $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$ iff
 $A \in S$ or some $B_i \notin S$ or some $C_j \in S$.

In English:

- S satisfies rule iff S satisfies the head or falsifies the body
- S falsifies body iff S falsifies some B_i or satisfies some C_j

Ex.: Let $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

Semantics: Interpretation

Definition: interpretation, satisfaction

An **interpretation** S is a set of atomic propositions.

S **satisfies** $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$ iff
 $A \in S$ or some $B_i \notin S$ or some $C_j \in S$.

In English:

- S satisfies rule iff S satisfies the head or falsifies the body
- S falsifies body iff S falsifies some B_i or satisfies some C_j

Ex.: Let $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S = \{a, b, c\}$ satisfies a , but it does not satisfy ($\text{not } b$).

Semantics: Interpretation

Definition: interpretation, satisfaction

An **interpretation** S is a set of atomic propositions.

S **satisfies** $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$ iff
 $A \in S$ or some $B_i \notin S$ or some $C_j \in S$.

In English:

- S satisfies rule iff S satisfies the head or falsifies the body
- S falsifies body iff S falsifies some B_i or satisfies some C_j

Ex.: Let $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S = \{a, b, c\}$ satisfies a , but it does not satisfy ($\text{not } b$).

It satisfies $c \leftarrow a, b$ because it satisfies the head because $c \in S$

Semantics: Interpretation

Definition: interpretation, satisfaction

An **interpretation** S is a set of atomic propositions.

S **satisfies** $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$ iff
 $A \in S$ or some $B_i \notin S$ or some $C_j \in S$.

In English:

- S satisfies rule iff S satisfies the head or falsifies the body
- S falsifies body iff S falsifies some B_i or satisfies some C_j

Ex.: Let $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S = \{a, b, c\}$ satisfies a , but it does not satisfy $(\text{not } b)$.

It satisfies $c \leftarrow a, b$ because it satisfies the head because $c \in S$

It satisfies $d \leftarrow a, \text{not } b$ because it falsifies the body because $b \in S$

Semantics without Negation

Definition: stable model for programs without negation

For P without negated literals:

S is a **stable model** of P iff

S is a minimal set (w.r.t. \subseteq) that satisfies all $r \in P$.

Semantics without Negation

Definition: stable model for programs without negation

For P without negated literals:

S is a **stable model** of P iff

S is a minimal set (w.r.t. \subseteq) that satisfies all $r \in P$.

Ex.: $P = \{a. \quad c \leftarrow a, b.\}$

Semantics without Negation

Definition: stable model for programs without negation

For P without negated literals:

S is a **stable model** of P iff

S is a minimal set (w.r.t. \subseteq) that satisfies all $r \in P$.

Ex.: $P = \{a. \quad c \leftarrow a, b.\}$

$S_1 = \{a\}$ is a stable model of P

Semantics without Negation

Definition: stable model for programs without negation

For P without negated literals:

S is a **stable model** of P iff

S is a minimal set (w.r.t. \subseteq) that satisfies all $r \in P$.

Ex.: $P = \{a. \quad c \leftarrow a, b.\}$

$S_1 = \{a\}$ is a stable model of P

$S_2 = \{a, b\}$ is not a stable model of P

Semantics without Negation

Definition: stable model for programs without negation

For P without negated literals:

S is a **stable model** of P iff

S is a minimal set (w.r.t. \subseteq) that satisfies all $r \in P$.

Ex.: $P = \{a. \quad c \leftarrow a, b.\}$

$S_1 = \{a\}$ is a stable model of P

$S_2 = \{a, b\}$ is not a stable model of P

$S_3 = \{a, b, c\}$ is not a stable model of P

Semantics without Negation

Definition: stable model for programs without negation

For P without negated literals:

S is a **stable model** of P iff

S is a minimal set (w.r.t. \subseteq) that satisfies all $r \in P$.

Ex.: $P = \{a. \quad c \leftarrow a, b.\}$

$S_1 = \{a\}$ is a stable model of P

$S_2 = \{a, b\}$ is not a stable model of P

$S_3 = \{a, b, c\}$ is not a stable model of P

Theorem: unique-model property

If P is negation-free (i.e., contains no $(\text{not } C)$), then there is exactly one stable model, which can be computed in linear time.

Semantics without Negation – Examples

Compute stable model of a negation-free P by *unit propagation*:

- $S^0 = \{\}$
- $S^{i+1} = S^i \cup \bigcup_{r \in P: S \text{ satisfies Body}(r)} \text{Head}(r)$ until $S^{i+1} = S^i$

Semantics without Negation – Examples

Compute stable model of a negation-free P by *unit propagation*:

- $S^0 = \{\}$
- $S^{i+1} = S^i \cup \bigcup_{r \in P: S \text{ satisfies Body}(r)} \text{Head}(r)$ until $S^{i+1} = S^i$

Ex.: $P_1 = \{a. \quad b \leftarrow a.\}$

$S^0 = \{\}$ $S^1 = \{a\}$ $S^2 = \{a, b\}$ Fixpoint

Semantics without Negation – Examples

Compute stable model of a negation-free P by *unit propagation*:

- $S^0 = \{\}$
- $S^{i+1} = S^i \cup \bigcup_{r \in P: S \text{ satisfies Body}(r)} \text{Head}(r)$ until $S^{i+1} = S^i$

Ex.: $P_1 = \{a. \quad b \leftarrow a.\}$

$S^0 = \{\}$ $S^1 = \{a\}$ $S^2 = \{a, b\}$ Fixpoint

Ex.: $P_2 = \{a \leftarrow b. \quad b \leftarrow a.\}$

$S^0 = \{\}$ Fixpoint

Semantics without Negation – Examples

Compute stable model of a negation-free P by *unit propagation*:

- $S^0 = \{\}$
- $S^{i+1} = S^i \cup \bigcup_{r \in P: S \text{ satisfies Body}(r)} \text{Head}(r)$ until $S^{i+1} = S^i$

Ex.: $P_1 = \{a. \quad b \leftarrow a.\}$

$S^0 = \{\}$ $S^1 = \{a\}$ $S^2 = \{a, b\}$ Fixpoint

Ex.: $P_2 = \{a \leftarrow b. \quad b \leftarrow a.\}$

$S^0 = \{\}$ Fixpoint

Ex.: $P_3 = \{a \leftarrow b. \quad b \leftarrow a. \quad a.\}$

$S^0 = \{\}$ $S^1 = \{a\}$ $S^2 = \{a, b\}$ Fixpoint

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Ex.: $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Ex.: $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_1 = \{a\} \quad \Rightarrow \quad P^{S_1} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Ex.: $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_1 = \{a\} \Rightarrow P^{S_1} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_2 = \{a, b\} \Rightarrow P^{S_2} = \{a. \quad c \leftarrow a, b. \quad \cancel{d \leftarrow a, \text{not } b.}\}$

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Ex.: $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_1 = \{a\} \Rightarrow P^{S_1} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_2 = \{a, b\} \Rightarrow P^{S_2} = \{a. \quad c \leftarrow a, b. \quad \text{d} \leftarrow \text{a}, \text{not } b.\}$

$S_3 = \{a, d\} \Rightarrow P^{S_3} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Ex.: $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_1 = \{a\} \Rightarrow P^{S_1} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

$S_2 = \{a, b\} \Rightarrow P^{S_2} = \{a. \quad c \leftarrow a, b.\}$

$S_3 = \{a, d\} \Rightarrow P^{S_3} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Ex.: $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_1 = \{a\} \Rightarrow P^{S_1} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

$S_2 = \{a, b\} \Rightarrow P^{S_2} = \{a. \quad c \leftarrow a, b.\}$

$S_3 = \{a, d\} \Rightarrow P^{S_3} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

Definition: stable model for programs with negation

For P with negated literals:

S is a **stable model** of P iff S is a stable model of P^S .

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Ex.: $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_1 = \{a\} \Rightarrow P^{S_1} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

$S_2 = \{a, b\} \Rightarrow P^{S_2} = \{a. \quad c \leftarrow a, b.\}$

$S_3 = \{a, d\} \Rightarrow P^{S_3} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

X

Definition: stable model for programs with negation

For P with negated literals:

S is a **stable model** of P iff S is a stable model of P^S .

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Ex.: $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_1 = \{a\} \Rightarrow P^{S_1} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

$S_2 = \{a, b\} \Rightarrow P^{S_2} = \{a. \quad c \leftarrow a, b.\}$

$S_3 = \{a, d\} \Rightarrow P^{S_3} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

✗

✗

Definition: stable model for programs with negation

For P with negated literals:

S is a **stable model** of P iff S is a stable model of P^S .

Semantics with Negation

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

In English: for each rule r from P ,

- if $(\text{not } C) \in \text{Body}(r)$ for some $C \in S$: drop the rule
- else: remove all negated literals and add to P^S

Ex.: $P = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a, \text{not } b.\}$

$S_1 = \{a\} \Rightarrow P^{S_1} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

✗

$S_2 = \{a, b\} \Rightarrow P^{S_2} = \{a. \quad c \leftarrow a, b.\}$

✗

$S_3 = \{a, d\} \Rightarrow P^{S_3} = \{a. \quad c \leftarrow a, b. \quad d \leftarrow a.\}$

✓

Definition: stable model for programs with negation

For P with negated literals:

S is a **stable model** of P iff S is a stable model of P^S .

Semantics with Negation – Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} =$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_2 = \{a\}$ $\Rightarrow P^{S_2} =$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a \leftarrow \text{not } b. \quad \text{b} \leftarrow \text{not } a.\}$

$S_3 = \{b\}$ $\Rightarrow P^{S_3} =$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a \leftarrow \text{not } b. \quad \text{b} \leftarrow \text{not } a.\}$

$S_3 = \{b\}$ $\Rightarrow P^{S_3} = \{\text{a} \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a \leftarrow \text{not } b. \quad \text{b} \leftarrow \text{not } a.\}$

$S_3 = \{b\}$ $\Rightarrow P^{S_3} = \{\text{a} \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_4 = \{a, b\}$ $\Rightarrow P^{S_4} =$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a \leftarrow \text{not } b. \quad \cancel{b \leftarrow \text{not } a.}\}$

$S_3 = \{b\}$ $\Rightarrow P^{S_3} = \{\cancel{a \leftarrow \text{not } b.} \quad b \leftarrow \text{not } a.\}$

$S_4 = \{a, b\}$ $\Rightarrow P^{S_4} = \{\cancel{a \leftarrow \text{not } b.} \quad \cancel{b \leftarrow \text{not } a.}\}$

Semantics with Negation – Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$$S_1 = \{\} \quad \Rightarrow \quad P^{S_1} = \{a. \quad b\}$$

$$S_2 = \{a\} \quad \Rightarrow \quad P^{S_2} = \{a.\}$$

$$S_3 = \{b\} \quad \Rightarrow \quad P^{S_3} = \{b.\}$$

$$S_4 = \{a, b\} \quad \Rightarrow \quad P^{S_4} = \{\}$$

Semantics with Negation – Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$$S_1 = \{\} \quad \Rightarrow \quad P^{S_1} = \{a. \quad b\}$$

$$S_2 = \{a\} \quad \Rightarrow \quad P^{S_2} = \{a.\}$$

$$S_3 = \{b\} \quad \Rightarrow \quad P^{S_3} = \{b.\}$$

$$S_4 = \{a, b\} \quad \Rightarrow \quad P^{S_4} = \{\}$$

X

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$$S_1 = \{\} \quad \Rightarrow \quad P^{S_1} = \{a. \quad b\}$$

$$S_2 = \{a\} \quad \Rightarrow \quad P^{S_2} = \{a.\}$$

$$S_3 = \{b\} \quad \Rightarrow \quad P^{S_3} = \{b.\}$$

$$S_4 = \{a, b\} \quad \Rightarrow \quad P^{S_4} = \{\}$$

~~X~~

✓

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$$S_1 = \{\} \quad \Rightarrow \quad P^{S_1} = \{a. \quad b\}$$

$$S_2 = \{a\} \quad \Rightarrow \quad P^{S_2} = \{a.\}$$

$$S_3 = \{b\} \quad \Rightarrow \quad P^{S_3} = \{b.\}$$

$$S_4 = \{a, b\} \quad \Rightarrow \quad P^{S_4} = \{\}$$







Semantics with Negation – Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$$S_1 = \{\} \quad \Rightarrow \quad P^{S_1} = \{a. \quad b\}$$

X

$$S_2 = \{a\} \quad \Rightarrow \quad P^{S_2} = \{a.\}$$

✓

$$S_3 = \{b\} \quad \Rightarrow \quad P^{S_3} = \{b.\}$$

✓

$$S_4 = \{a, b\} \quad \Rightarrow \quad P^{S_4} = \{\}$$

X

Two stable models!

Semantics with Negation – Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a. \quad b\}$

X

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a.\}$

✓

$S_3 = \{b\}$ $\Rightarrow P^{S_3} = \{b.\}$

✓

$S_4 = \{a, b\}$ $\Rightarrow P^{S_4} = \{\}$

X

Two stable models!

Ex.: $P = \{a \leftarrow \text{not } a.\}$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a. \quad b\}$

X

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a.\}$

✓

$S_3 = \{b\}$ $\Rightarrow P^{S_3} = \{b.\}$

✓

$S_4 = \{a, b\}$ $\Rightarrow P^{S_4} = \{\}$

X

Two stable models!

Ex.: $P = \{a \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} =$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a. \quad b\}$

X

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a.\}$

✓

$S_3 = \{b\}$ $\Rightarrow P^{S_3} = \{b.\}$

✓

$S_4 = \{a, b\}$ $\Rightarrow P^{S_4} = \{\}$

X

Two stable models!

Ex.: $P = \{a \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } a.\}$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a. \quad b\}$

X

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a.\}$

✓

$S_3 = \{b\}$ $\Rightarrow P^{S_3} = \{b.\}$

✓

$S_4 = \{a, b\}$ $\Rightarrow P^{S_4} = \{\}$

X

Two stable models!

Ex.: $P = \{a \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } a.\}$

$S_2 = \{a\}$ $\Rightarrow P^{S_2} =$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a. \quad b\}$

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a.\}$

$S_3 = \{b\}$ $\Rightarrow P^{S_3} = \{b.\}$

$S_4 = \{a, b\}$ $\Rightarrow P^{S_4} = \{\}$

Two stable models!

X

✓

✓

X

Ex.: $P = \{a \leftarrow \text{not } a.\}$

$S_1 = \{\}$ $\Rightarrow P^{S_1} = \{a \leftarrow \text{not } a.\}$

$S_2 = \{a\}$ $\Rightarrow P^{S_2} = \{a \leftarrow \text{not } a.\}$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$$S_1 = \{\} \quad \Rightarrow \quad P^{S_1} = \{a. \quad b\}$$

$$S_2 = \{a\} \quad \Rightarrow \quad P^{S_2} = \{a.\}$$

$$S_3 = \{b\} \quad \Rightarrow \quad P^{S_3} = \{b.\}$$

$$S_4 = \{a, b\} \quad \Rightarrow \quad P^{S_4} = \{\}$$

Two stable models!

X

✓

✓

X

Ex.: $P = \{a \leftarrow \text{not } a.\}$

$$S_1 = \{\} \quad \Rightarrow \quad P^{S_1} = \{a.\}$$

$$S_2 = \{a\} \quad \Rightarrow \quad P^{S_2} = \{\}$$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$$S_1 = \{\} \quad \Rightarrow \quad P^{S_1} = \{a. \quad b\}$$

✗

$$S_2 = \{a\} \quad \Rightarrow \quad P^{S_2} = \{a.\}$$

✓

$$S_3 = \{b\} \quad \Rightarrow \quad P^{S_3} = \{b.\}$$

✓

$$S_4 = \{a, b\} \quad \Rightarrow \quad P^{S_4} = \{\}$$

✗

Two stable models!

Ex.: $P = \{a \leftarrow \text{not } a.\}$

$$S_1 = \{\} \quad \Rightarrow \quad P^{S_1} = \{a.\}$$

✗

$$S_2 = \{a\} \quad \Rightarrow \quad P^{S_2} = \{\}$$

Semantics with Negation - Examples

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } a.\}$

$$S_1 = \{\} \Rightarrow P^{S_1} = \{a. \quad b\}$$

✗

$$S_2 = \{a\} \Rightarrow P^{S_2} = \{a.\}$$

✓

$$S_3 = \{b\} \Rightarrow P^{S_3} = \{b.\}$$

✓

$$S_4 = \{a, b\} \Rightarrow P^{S_4} = \{\}$$

✗

Two stable models!

Ex.: $P = \{a \leftarrow \text{not } a.\}$

$$S_1 = \{\} \Rightarrow P^{S_1} = \{a.\}$$

✗

$$S_2 = \{a\} \Rightarrow P^{S_2} = \{\}$$

✗

No stable model!

Semantics: Overview

Definition: reduct

The **reduct** P^S of P relative to S is the least set such that
if $A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n \in P$ and $C_1, \dots, C_n \notin S$
then $A \leftarrow B_1, \dots, B_m \in P^S$.

Definition: stable model

If P contains no (not C):

S is a **stable model** of P iff

S is a minimal set (w.r.t. \subseteq) that satisfies all $r \in P$.

If P contains (not C):

S is a **stable model** of P iff S is a stable model of P^S .

Theorem: necessary satisfaction condition

If S is a stable model and $A \in S$,

then S satisfies some $r \in P$ with $A \in \text{Head}(r)$.

Semantics – Examples

Ex.: $P = \{a \leftarrow a. \quad b \leftarrow \text{not } a.\}$

S

P^S

Stable model?

Ex.: $P = \{a \leftarrow \text{not } b. \quad b \leftarrow \text{not } c.\}$

S

P^S

Stable model?

Example on paper

Overview of the Lecture

- Semantics of ASP programs
- **Extensions of ASP programs**
- Handling of variables in ASP
- ASP as modelling language

Integrity Constraints

Definition: integrity constraint

An **integrity constraint** is a rule r of the form

$$\leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$$

S **satisfies** r iff some $B_i \notin S$ or some $C_j \in S$.

P^S contains $\leftarrow B_1, \dots, B_m$ iff P contains r and $C_1, \dots, C_n \notin S$.

Integrity Constraints

Definition: integrity constraint

An **integrity constraint** is a rule r of the form

$$\leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$$

S **satisfies** r iff some $B_i \notin S$ or some $C_j \in S$.

P^S contains $\leftarrow B_1, \dots, B_m$ iff P contains r and $C_1, \dots, C_n \notin S$.

Theorem: reduction to normal rules

Let P' be like P except that every integrity constraint

$$\leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$$

is replaced with

$$\text{dummy} \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n, \text{not } \text{dummy}$$

for some new atom *dummy*.

Then P and P' have the same stable models.

Choice Rules

Definition: choice rule

A **choice rule** is a rule the form

$$\{A_1, \dots, A_k\} \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$$

which allows any subset of $\{A_1, \dots, A_k\}$ in a stable model.

Choice Rules

Definition: choice rule

A **choice rule** is a rule the form

$$\{A_1, \dots, A_k\} \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$$

which allows any subset of $\{A_1, \dots, A_k\}$ in a stable model.

Theorem: reduction to normal rules

A choice rule can be encoded by $2k + 1$ normal rules using $2k + 1$ new atoms.

Choice Rules

Definition: choice rule

A **choice rule** is a rule the form

$$\{A_1, \dots, A_k\} \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$$

which allows any subset of $\{A_1, \dots, A_k\}$ in a stable model.

Theorem: reduction to normal rules

A choice rule can be encoded by $2k + 1$ normal rules using $2k + 1$ new atoms.

Further extensions:

- Conditional literals: $\{A : B\}$
Ex.: $\{m(v, C) : c(C)\}$ expands to $\{m(v, r), m(v, g), m(v, b)\}$
- Cardinality constraints: $\min \{A_1, \dots, A_k\} \max$
Ex.: $1 \{m(v, r), m(v, g), m(v, b)\} 1$

Negation in the Rule Head

Definition: rules with negated head

A rule with **negated head** is of the form

$$\text{not } A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$$

Negation in the Rule Head

Definition: rules with negated head

A rule with **negated head** is of the form

$$\text{not } A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$$

Theorem: reduction to normal rules

Let P' be like P except that every rule with negated head

$$\text{not } A \leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n$$

is replaced with

$$\leftarrow B_1, \dots, B_m, \text{not } C_1, \dots, \text{not } C_n, \text{not } \textit{dummy}$$

and

$$\textit{dummy} \leftarrow \text{not } A$$

for some new atom *dummy*.

Then P and P' have the same stable models (modulo dummy propositions).

Complexity

Theorem: complexity of NLPs without negations

Is S a stable model of a negation-free P ? – **Linear time**

Does a negation-free P have a stable model? – **Constant** (yes, one)

Theorem: complexity of NLPs with negations

Is S a stable model of P ? – **Linear time**

Does P have a stable model? – **NP-complete**

Note: integrity constraints, choice rules, negation in heads
preserve complexity (program grows only polynomially)

Overview of the Lecture

- Semantics of ASP programs
- Extensions of ASP programs
- **Handling of variables in ASP**
- ASP as modelling language

Programs with Variables

- Atomic propositions may now contain variables, e.g.,
 $p(X, Z) \leftarrow e(X, Y), p(Y, Z)$.

Programs with Variables

- Atomic propositions may now contain variables, e.g.,
 $p(X, Z) \leftarrow e(X, Y), p(Y, Z)$.
- Herbrand universe
 - ▶ U contains all constants from P
 - ▶ U contains all $f(t_1, \dots, t_k)$ from P if f is a k -ary function in P and U contains t_1, \dots, t_k

Programs with Variables

- Atomic propositions may now contain variables, e.g.,
 $p(X, Z) \leftarrow e(X, Y), p(Y, Z)$.
- Herbrand universe
 - ▶ U contains all constants from P
 - ▶ U contains all $f(t_1, \dots, t_k)$ from P if f is a k -ary function in P and U contains t_1, \dots, t_k
- ASP **grounds** variables with Herbrand universe
 - ▶ Unlike Prolog: instantiation instead of unification
 - ▶ Caution: the ground program may grow exponentially
 - ▶ Caution: function symbols make grounding Turing-complete
 - ▶ If P is finite and mentions only constants, grounding is finite

Programs with Variables

- $f(X) \leftarrow b(X)$, not $a(X)$.
 $a(X) \leftarrow p(X)$.
 $b(\text{sam})$.
 $b(\text{tweety})$.
 $p(\text{tweety})$.
- $f(\text{sam}) \leftarrow b(\text{sam})$, not $a(\text{sam})$.
 $f(\text{tweety}) \leftarrow b(\text{tweety})$, not $a(\text{tweety})$.
 $a(\text{sam}) \leftarrow p(\text{sam})$.
 $a(\text{tweety}) \leftarrow p(\text{tweety})$.
 $b(\text{sam})$.
 $b(\text{tweety})$.
 $p(\text{tweety})$.

Overview of the Lecture

- Semantics of ASP programs
- Extensions of ASP programs
- Handling of variables in ASP
- **ASP as modelling language**

ASP Modelling

$c(r). c(g). c(b).$
 $v(1). \dots v(6).$
 $e(1, 2). e(1, 3). e(1, 4).$
 $e(2, 4). e(2, 5). e(2, 6).$
 $e(3, 1). e(3, 4). e(3, 5).$
 $e(4, 1). e(4, 2).$
 $e(5, 3). e(5, 4). e(5, 6).$
 $e(6, 2). e(6, 3). e(6, 5).$

Typical ASP structure:

- Problem **instance**: a set of facts
- Problem **class**: a set of rules

- ▶ Generator rules: often choice rules $\{m(X, C) : c(C)\} 1 :- v(X).$
- ▶ Test rules: often integrity constraints $:- e(X, Y), m(X, C), m(Y, C).$

Ideal modeling is **uniform**: problem class encoding fits all instances

Semantically equivalent encodings may differ immensely in performance!

Example: Non-monotonic Reasoning

Tweety the penguin:

- (Normal) Birds fly.
- Penguins are abnormal.
- Tweety is a bird. So Tweety flies.
- Tweety is a penguin. So Tweety doesn't fly.

Example: Non-monotonic Reasoning

Tweety the penguin:

- (Normal) Birds fly.
- Penguins are abnormal.
- Tweety is a bird. So Tweety flies.
- Tweety is a penguin. So Tweety doesn't fly.

$$U = \{f(X) \leftarrow b(X), \text{not } a(X). \quad a(X) \leftarrow p(X). \quad b(t).\}$$
$$P = \{f(t) \leftarrow b(t), \text{not } a(t). \quad a(t) \leftarrow p(t). \quad b(t).\}$$

Example: Non-monotonic Reasoning

Tweety the penguin:

- (Normal) Birds fly.
- Penguins are abnormal.
- Tweety is a bird. So Tweety flies.
- Tweety is a penguin. So Tweety doesn't fly.

$U = \{f(X) \leftarrow b(X), \text{not } a(X). \quad a(X) \leftarrow p(X). \quad b(t).\}$

$P = \{f(t) \leftarrow b(t), \text{not } a(t). \quad a(t) \leftarrow p(t). \quad b(t).\}$

$S_1 = \{b(t), f(t)\} \Rightarrow P^{S_1} = \{f(t) \leftarrow b(t), \text{not } a(t). \quad a(t) \leftarrow p(t). \quad b(t).\}$ ✓

$S_2 = \{a(t), b(t), p(t)\} \Rightarrow P^{S_2} = \{f(t) \leftarrow b(t), \text{not } a(t). \quad a(t) \leftarrow p(t). \quad b(t).\}$ ✗

Tweety flies!

Example: Non-monotonic Reasoning

Tweety the penguin:

- (Normal) Birds fly.
- Penguins are abnormal.
- Tweety is a bird. ~~So Tweety flies.~~
- Tweety is a penguin. So Tweety doesn't fly.

$U = \{f(X) \leftarrow b(X), \text{not } a(X). \quad a(X) \leftarrow p(X). \quad b(t).\}$

$P = \{f(t) \leftarrow b(t), \text{not } a(t). \quad a(t) \leftarrow p(t). \quad b(t).\}$

$S_1 = \{b(t), f(t)\} \Rightarrow P^{S_1} = \{f(t) \leftarrow b(t), \text{not } a(t). \quad a(t) \leftarrow p(t). \quad b(t).\}$ ✓

$S_2 = \{a(t), b(t), p(t)\} \Rightarrow P^{S_2} = \{f(t) \leftarrow b(t), \text{not } a(t). \quad a(t) \leftarrow p(t). \quad b(t).\}$ ✗

Tweety flies!

$S_1 = \{b(t), f(t)\} \Rightarrow (P \cup \{p(t).\})^{S_1} = P_2^{S_1} \cup \{p(t).\}$ ✗


$S_2 = \{a(t), b(t), p(t)\} \Rightarrow (P \cup \{p(t).\})^{S_2} = P_2^{S_1} \cup \{p(t).\}$ ✓

Tweety doesn't fly.

Example: Hamilton Cycle

Definition: Hamilton cycle problem

Input: graph with vertex set V and edges $E \subseteq V \times V$.
Is there a cycle that visits every vertex exactly once?




$$\begin{aligned} \{p(X, Y)\} &\leftarrow e(X, Y). \\ r(X) &\leftarrow p(1, X). \\ r(Y) &\leftarrow r(X), p(X, Y). \\ &\leftarrow 2 \{p(X, Y)\}, v(X). \\ &\leftarrow 2 \{p(X, Y)\}, v(Y). \\ &\leftarrow \text{not } r(X), v(X). \end{aligned}$$

Example: Hamilton Cycle

Definition: Hamilton cycle problem


Input: graph with vertex set V and edges $E \subseteq V \times V$.
Is there a cycle that visits every vertex exactly once?


$$\{p(X, Y)\} \leftarrow e(X, Y).$$
$$r(X) \leftarrow p(1, X).$$
$$r(Y) \leftarrow r(X), p(X, Y).$$
$$\leftarrow 2 \{p(X, Y)\}, v(X).$$
$$\leftarrow 2 \{p(X, Y)\}, v(Y).$$
$$\leftarrow \text{not } r(X), v(X).$$

Example: N -Queens

Definition: N -queens problem

Place N queens on a $N \times N$ chessboard so that they do not attack each other, i.e., share no row, column, or diagonal.




Program on paper

Example: N -Queens

Definition: N -queens problem

Place N queens on a $N \times N$ chessboard so that they do not attack each other, i.e., share no row, column, or diagonal.



Program on paper