#### **Lab: Programming Practices and Graph Algorithms**

Week 1

Yulei Sui

School of Computer Science and Engineering University of New South Wales, Australia

### What to Expect from Each Lab

#### What We Do:

- Lab demonstrations, including configuring IDEs, coding examples, and further explanations of concepts from lectures.
- Reinforce your skills and knowledge to complete lab exercises and assignments.
- Answer questions regarding specifications in your exercises and assignments.
- Provide time for you to work on your quizzes and coding exercises.

#### What We Don't Do:

- Debug your program
- Teach programming. This course does NOT focus on teaching you C++ or Python, but this lab provides a brief guide. Completing assessments requires basic C++ (recommended) or Python syntax/knowledge.
- Give you code solutions or judge the correctness of your exercise/assignment.

**No sharing** of your solutions in the forums or public GitHub repositories.

#### Quiz-1 and Exercise-1

• Lab-Quiz-1:

https://webcms3.cse.unsw.edu.au/COMP6131/25T2/resources/112317

- C++ programming, software vulnerability assessment, compiler, control-flow, data-flow, and taint tracking.
- 25 quizzes (each worth 0.2 marks) covering knowledge taught in Week 1 and Week 2.
- Lab-Exercise-1: https://github.com/SVF-tools/ Software-Security-Analysis/wiki/Lab-Exercise-1
  - Implementing the reachability method, a DFS graph traversal algorithm.
  - Implementing the solveWorklist method, a constraint graph solving algorithm for Andersen's points-to analysis: https://github.com/SVF-tools/ Software-Security-Analysis/blob/slides/1.lab-andersen.pdf

Submit your Quiz-1 and Lab-Exercise-1 on WebCMS by 23:59 on Tuesday of Week 3.

#### Today's Lab: IDE Demo and Introduction/Revisit to C++/Python

- Configure your programming environment: https://github.com/SVF-tools/ Software-Security-Analysis/wiki/Configure-IDE
  - Start writing the 'hello world' program.
  - Experiment with the code snippets in today's slides to explore or revisit C++/Python features.
- Quick introduction/revisit C++/Python programming
  - Data types
  - classes, objects, containers and collections
  - · Pointers and references
  - Functions and inheritance
- Working on your Quiz-1 and Exercise-1

#### A Quick Overview of C++

#### Week 1

#### Yulei Sui

School of Computer Science and Engineering University of New South Wales, Australia

What is C++?

 A general-purpose programming language that was developed as an enhancement of the C language to include object-oriented paradigm.

#### What is C++?

 A general-purpose programming language that was developed as an enhancement of the C language to include object-oriented paradigm.

#### Why learn C++?

 Language for building system software (e.g., operating systems, web browsers, game engines, database engines, language runtimes and cloud/distributed systems)

#### What is C++?

 A general-purpose programming language that was developed as an enhancement of the C language to include object-oriented paradigm.

#### Why learn C++?

- Language for building system software (e.g., operating systems, web browsers, game engines, database engines, language runtimes and cloud/distributed systems)
- Object-oriented yet high performance
- Pointer and direct memory-access

#### What is C++?

 A general-purpose programming language that was developed as an enhancement of the C language to include object-oriented paradigm.

#### Why learn C++?

- Language for building system software (e.g., operating systems, web browsers, game engines, database engines, language runtimes and cloud/distributed systems)
- Object-oriented yet high performance
- Pointer and direct memory-access
- One of the most popular languages and fastest-growing
  - www.techrepublic.com/article/c-is-now-the-fastest-growing-programming-language
  - www.techrepublic.com/article/ most-popular-programming-languages-c-knocks-python-out-of-top-three

• This short introduction does not aim to cover every detailed aspect of C++, but rather the basic C++ syntax/features in order to develop algorithms to fulfil the assignment tasks in this course.

- This short introduction does not aim to cover every detailed aspect of C++, but rather the basic C++ syntax/features in order to develop algorithms to fulfil the assignment tasks in this course.
- You are encouraged to learn and practice more advanced C++ syntax/features.
  - https://www.w3schools.com/cpp/cpp\_intro.asp
  - https://www.youtube.com/watch?v=BClS40yzssA
  - Google search 'C++ programming' or 'introduction to C++ programming'

#### Write Your First C++ Program

```
#include <iostream>
using namespace std;
int main() {
  cout << "Hello World! \n";
  return 0;
}</pre>
```

A Hello World example under Software-Security-Analysis:

https://github.com/SVF-tools/Software-Security-Analysis/blob/main/HelloWorld/hello.cpp

#### C++ Primitive Data Types and Variables

- 'type variable = value; '
  - Primitive types including int, float, double, char, bool, string.

#### C++ Classes and Objects

- C++ class: new data type compared with C for
  - Abstraction: "shows" essential attributes and "hides" unnecessary information
  - Encapsulation: 'expose' only the interfaces and hide implementation details
- A C++ class is a template for objects, and an object is an instance of a class.

### C++ Classes and Objects

- C++ class: new data type compared with C for
  - Abstraction: "shows" essential attributes and "hides" unnecessary information
  - Encapsulation: 'expose' only the interfaces and hide implementation details
- A C++ class is a template for objects, and an object is an instance of a class.

```
#include <iostream>
using namespace std;
class Graph { // the class
 private: // private access specifier
   int numOfNodes; // hidden attribute from outside
   int numOfEdges: // hidden attribute from outside
 public:
              // public access specifier
   // interface to outside world
   int getNumOfNodes(){ return numOfNodes:}
   // interface to outside world
   void setNumOfNodes(int n){ numOfNodes = n:}
};
```

### C++ Classes and Objects

- C++ class: new data type compared with C for
  - Abstraction: "shows" essential attributes and "hides" unnecessary information
  - Encapsulation: 'expose' only the interfaces and hide implementation details
- A C++ class is a template for objects, and an object is an instance of a class.

```
#include <instream>
using namespace std;
                                                    int main() {
class Graph { // the class
                                                      // create an object of Graph
 private: // private access specifier
                                                      Graph graphObj:
   int numOfNodes; // hidden attribute from outside
                                                      // Access attribute via interface
    int numOfEdges: // hidden attribute from outside
                                                      graphObj.setNumOfNodes(10);
  public:
              // public access specifier
                                                      // print out value of the attribute
   // interface to outside world
                                                      cout << graphObj.getNumOfNodes();</pre>
    int getNumOfNodes(){ return numOfNodes:}
                                                      cout << "\n":
   // interface to outside world
   void setNumOfNodes(int n){ numOfNodes = n:}
};
```

#### Constructor

 A constructor is a special method automatically called when an object is created.

```
#include <iostream>
using namespace std;
class Graph { // the class
  private: // private access specifier
                                                   int main() {
    int numOfNodes; // hidden attribute from outside
                                                     // Create an object via its constructor
    int numOfEdges; // hidden attribute from outside
                                                     Graph graphObj(5,10);
  public:
              // public access specifier
                                                     // print out value of the attribute
     Graph(int n, int e){ // constructor
                                                     cout << graphObj.getNumOfNodes();</pre>
       numOfNodes = n:
                                                      cout << "\n":
       numOfEdges = e;
    // interface to outside world
    int getNumOfNodes(){ return numOfNodes:}
}:
```

#### **Containers/Collections**

A container is an object that stores a collection of elements.

- Standard container type
  - Plain C array int myNum[3] = {10, 20, 30};
- C++ STL container types.
  - Sequence containers (data structures accessed sequentially)
    - vector: Dynamic contiguous array (class template)
    - deque: Double-ended queue (class template)
    - list: Doubly-linked list (class template)
    - stack: Last In First Out (class template)
  - Associative containers (sorted data structures that can be quickly searched)
    - set: Collection of unique keys, sorted by keys (class template)
    - map: Collection of key-value pairs, sorted by keys, keys are unique (class template).

#### **Containers/Collections**

```
#include <vector>
#include <iostream>
using namespace std;
int main ()
  vector<int> nodeIDs;
  nodeIDs.push_back(1);
 nodeIDs.push_back(2);
 nodeIDs.push_back(2);
 // iterating elements via loop
  for(auto i : nodeIDs)
    cout << i << "\n":
```

#### **Containers/Collections**

```
#include <vector>
#include <iostream>
using namespace std;
int main ()
  vector<int> nodeIDs;
  nodeIDs.push_back(1);
  nodeIDs.push_back(2);
  nodeIDs.push_back(2):
  // iterating elements via loop
  for(auto i : nodeIDs)
    cout << i << "\n":
```

```
#include <set>
#include <iostream>
using namespace std;
int main ()
  set<int> nodeIDs:
 nodeIDs.insert(1):
 nodeIDs.insert(2):
 nodeIDs.insert(2):
 // iterating elements via loop
  for(auto i : nodeIDs)
    cout << i << "\n":
```

#### **Containers/Collections Used in a Class**

```
#include <set>
using namespace std;
class Graph {
 private:
    int numOfNodes;
    int numOfEdges;
    set<int> nodeIDs;
 public:
    Graph(int n, int e) {
        numOfNodes = n;
        numOfEdges = e;
    void addNode(int id){
        nodeIDs.insert(id);
};
```

```
int main() {
  // Create an object of Graph
 Graph graphObj(5,10);
  // Increase nodes;
  graphObj.addNode(1);
  graphObj.addNode(2);
```

### **Pointers for Primitive Types**

- The memory address of a variable can be taken through the & operator.
- A pointer however, is a variable that stores the memory address as its value.

```
int nodeID = 5; // A nodeID variable of type int
int* ptr = &nodeID;  // A pointer `ptr` storing the address of nodeID
cout << nodeID << "\n":
cout << &nodeID << "\n":
cout << ptr << "\n":
cout << *ptr << "\n":
```

### **Pointers for Primitive Types**

- The memory address of a variable can be taken through the & operator.
- A pointer however, is a variable that stores the memory address as its value.

```
int nodeID = 5; // A nodeID variable of type int
int* ptr = &nodeID;  // A pointer `ptr` storing the address of nodeID
// Output the value of NodeID (i.e., 5)
cout << nodeID << "\n":
// Output the memory address of NodeID (e.g., Ox6dfed4)
cout << &nodeID << "\n":
// Output the memory address of nodeID with the pointer (e.g., Ox6dfed4)
cout << ptr << "\n":
// Output the value of nodeID via dereferencing the pointer ptr
cout << *ptr << "\n":
```

### **References for Primitive Types**

 When a variable is declared as a reference, it becomes an alternative name for an existing variable. A variable can be declared as a reference by putting '&' in the declaration.

```
int nodeID = 5;  // A nodeID variable of type int
int& ref = nodeID;  // `ref` is a reference to nodeID.

ref = 20;
cout << "nodeID = " << nodeID << endl;

nodeID = 30;
cout << "ref = " << ref << endl;</pre>
```

### **References for Primitive Types**

 When a variable is declared as a reference, it becomes an alternative name for an existing variable. A variable can be declared as a reference by putting '&' in the declaration.

```
int nodeID = 5;  // A nodeID variable of type int
int& ref = nodeID;  // `ref` is a reference to nodeID.

ref = 20;  // Value of nodeID is now changed to 20
cout << "nodeID = " << nodeID << endl;

nodeID = 30;  // Both nodeID and ref are now 30
cout << "ref = " << ref << endl;</pre>
```

### C++ const Type Qualifier

• The **const** keyword allows you to specify whether or not a variable is modifiable. It can help (1) document your program more clearly and (2) enable more compiler optimization opportunities.

```
// a constant integer.
// modifying `nodeID` will get a compilation error.
const int nodeID = 5;
// pointer to a const variable.
// `ptr` is a pointer that can point to a const int type variable.
// modifying `nodeID` via `*ptr` will get a compilation error.
const int* ptr = &nodeID;
// const Pointer.
// `cptr` is a pointer, which is const, that points to an int.
// modifying `cptr` will get a compilation error
int anotherNodeID = 6:
int* const cptr = &anotherNodeID:
```

 Both references and pointers can be used to change local variables of one function inside another function.

```
/// parameters as values
/// (pass by value)
void swap(int n1, int n2){
    int tmp = n1;
    n1 = n2;
    n2 = tmp;
}
int main(){
    int node1 = 2, node2 = 3;
    swap(node1, node2);
    cout << node1 << " " << node2;
}</pre>
```

 Both references and pointers can be used to change local variables of one function inside another function

```
/// parameters as values
/// (pass by value)
void swap(int n1, int n2){
    int tmp = n1;
    n1 = n2:
    n2 = tmp:
int main(){
  int node1 = 2, node2 = 3;
  swap(node1, node2);
  cout << node1 << " " << node2:
```

pass by value: caller and callee have two independent variables with the same value (effect not visible to caller)

 Both references and pointers can be used to change local variables of one function inside another function.

```
/// parameters as values /// parameters as references
/// (pass by value)
                        /// (Pass by reference)
void swap(int n1, int n2){
void swap(int& n1, int& n2){
   int tmp = n1;
                               int tmp = n1;
                               n1 = n2:
   n1 = n2:
   n2 = tmp:
                               n2 = tmp:
int main(){
                            int main(){
 swap(node1, node2);
                             swap(node1, node2);
 cout << node1 << " " << node2:
                             cout << node1 << " " << node2:
```

pass by value: caller and callee have two independent variables with the same value (effect not visible to caller)

 Both references and pointers can be used to change local variables of one function inside another function.

```
/// parameters as values /// parameters as references
/// (pass by value)
                             /// (Pass by reference)
void swap(int n1, int n2){
void swap(int& n1, int& n2){
   int tmp = n1;
                                     int tmp = n1;
   n1 = n2;
                                     n1 = n2:
   n2 = tmp;
                                     n2 = tmp:
int main(){
                                 int main(){
                                   int node1 = 2, node2 = 3;
  int node1 = 2, node2 = 3;
  swap(node1, node2);
                                   swap(node1, node2);
  cout << node1 << " " << node2:
                                   cout << node1 << " " << node2:
pass by value: caller and callee have
                                 passed by reference: caller and
```

pass by value: caller and callee have two independent variables with the same value (effect not visible to caller) passed by reference: caller and callee share the same variable for the parameter (effect visible to caller)

 Both references and pointers can be used to change local variables of one function inside another function

```
/// parameters as values
/// (pass by value)
   int tmp = n1;
   n1 = n2:
   n2 = tmp:
int main(){
  int node1 = 2, node2 = 3;
  swap(node1, node2);
  cout << node1 << " " << node2:
```

pass by value: caller and callee have two independent variables with the same value (effect not visible to caller)

```
/// parameters as references /// parameters as pointers
                           /// (Pass by reference) /// (Pass by pointers)
void swap(int n1, int n2){
void swap(int& n1, int& n2){
                                 int tmp = n1;
                                 n1 = n2:
                                 n2 = tmp:
                              int main(){
                                int node1 = 2, node2 = 3;
                                swap(node1, node2);
                                cout << node1 << " " << node2:
```

passed by reference: caller and callee share the same variable for the parameter (effect visible to caller)

```
void swap(int* n1, int* n2){
    int tmp = *n1;
    *n1 = *n2:
    *n2 = tmp:
int main(){
  int node1 = 2, node2 = 3;
  swap (&node1, &node2);
  cout << node1 << " " << node2:
```

 Both references and pointers can be used to change local variables of one function inside another function

```
/// parameters as values
/// (pass by value)
    int tmp = n1;
   n1 = n2:
   n2 = tmp:
int main(){
  int node1 = 2, node2 = 3;
  swap(node1, node2);
  cout << node1 << " " << node2:
```

pass by value: caller and callee have two independent variables with the same value (effect not visible to caller)

```
/// parameters as references /// parameters as pointers
                            /// (Pass by reference)
void swap(int n1, int n2){
void swap(int n1, int n2){
                                  int tmp = n1;
                                  n1 = n2:
                                  n2 = tmp:
                              int main(){
                                int node1 = 2, node2 = 3;
                                swap(node1, node2);
                                cout << node1 << " " << node2:
```

passed by reference: caller and callee share the same variable for the parameter (effect visible to caller)

```
/// (Pass by pointers)
void swap(int* n1, int* n2){
    int tmp = *n1;
    *n1 = *n2:
    *n2 = tmp:
int main(){
  int node1 = 2, node2 = 3;
  swap (&node1, &node2);
  cout << node1 << " " << node2:
```

pass by pointer: caller and callee share the same variable via pointer dereferences (effect visible to caller)

 Both of them can also be used to save copying of big objects when passed as arguments to functions or returned from functions, to be more efficient.

```
class Graph {
public:
   int numOfNodes;
   int numOfEdges;
};
// If we remove `*` or `&` in below functions, a new copy of the graph object is created.
// `const` used to avoid accidentally updates `q` as the purpose is to print `q` only.
void print(const Graph *g){
    cout << g->numOfNodes << " " << g->numOfEdges << " ";</pre>
void print(const Graph &g){
    cout << g.numOfNodes << " " << g.numOfEdges << " ";</pre>
```

#### **Using Pointers in Classes**

```
#include <iostream>
using namespace std;
class Node { // The class
 private:
    int nodeID; // Node ID
 public: // Access specifier
    Node(int i){ nodeID = i; } // constructor
   int getNodeID() { return nodeID;}
};
class Edge { // The class
 private: // Access specifier
   Node* src; // source node of an edge
    Node* dst; // target node of an edge
  public:
    Edge(Node* s, Node* d){ // constructor
       src = s: dst = d:
    Node* getSrc() { return src;}
    Node* getDst() { return dst;}
};
```

#### **Using Pointers in Classes**

```
#include <iostream>
using namespace std;
class Node { // The class
 private:
    int nodeID; // Node ID
 public: // Access specifier
    Node(int i){ nodeID = i; } // constructor
   int getNodeID() { return nodeID;}
};
class Edge { // The class
 private: // Access specifier
   Node* src; // source node of an edge
    Node* dst; // target node of an edge
  public:
    Edge(Node* s, Node* d){ // constructor
       src = s: dst = d:
    Node* getSrc() { return src;}
    Node* getDst() { return dst;}
};
```

```
int main () {
Node* srcNode = new Node(1):
Node* dstNode = new Node(2):
// Assess public member functions or attributes
// through field access `->` operator
// similar to pointer dereferences
cout << srcNode->getNodeID() << " ";</pre>
cout << dstNode->getNodeID() << "\n";</pre>
Edge* edge = new Edge(srcNode,dstNode);
 cout << edge->getSrc()->getNodeID() << " ";</pre>
cout << edge->getDst()->getNodeID() << "\n";</pre>
```

# Putting All the Above Classes Together to Build a Graph

```
using namespace std; class Edge;
                                                class Graph {
                                                                       // The class
class Node {
                                                  private:
                                                                       // Access specifier
 private:
                                                    set < Node *> nodes: // a set of nodes
   int nodeID:
                                                  public:
                                                    Graph() { } // constructor
   set<Edge*> outEdges; // outgoing edges
 public:
                                                    set<Node*>& getNodes(){ return nodes;}
   Node(int i) { nodeID = i; }
                                                }:
   int getNodeID() { return nodeID;}
   set<Edge*>& getOutEdges(){ return outEdges;}
};
class Edge {
 private:
   Node* src:
   Node* dst;
 public:
   Edge(Node* s,Node* d){  src = s; dst = d; }
   Node* getSrc() { return src:}
   Node* getDst() { return dst;}
}:
```

## Putting All the Above Classes Together to Build a Graph

```
#include <set>
                                                  class Graph {
using namespace std; class Edge;
                                                    private:
class Node {
                                                      set<Node*> nodes: // a set of nodes
 private:
                                                    public:
    int nodeID:
                                                      Graph() { }
    set<Edge*> outEdges: // outgoing edges
                                                      set<Node*>& getNodes(){ return nodes;}
 public:
                                                  };
    Node(int i) { nodeID = i; }
                                                  int main () {
    int getNodeID() { return nodeID;}
                                                   Node* src = new Node(1);
    set<Edge*>& getOutEdges(){ return outEdges;}
                                                   Node* dst = new Node(2):
};
                                                   Edge* edge = new Edge(src, dst);
                                                   // add src's outgoing edge
class Edge {
                                                   src->getOutEdges().insert(edge);
 private:
                                                    // create a graph object
    Node* src:
                                                   Graph* graph = new Graph():
    Node* dst;
                                                   // add two nodes into the graph
 public:
                                                   graph->getNodes().insert(src);
    Edge(Node* s,Node* d){  src = s; dst = d; }
                                                   graph->getNodes().insert(dst);
    Node* getSrc() { return src:}
    Node* getDst() { return dst;}
}:
```

#### C++ Inheritance

Allow a child class to inherit attributes and methods from its parent class.

#### C++ Inheritance

Allow a child class to inherit attributes and methods from its parent class.

```
class GraphBuilder{
public:
    GraphBuilder(){}
    void build(){
        cout << "parent's way to build..\n";</pre>
        Node* src = new Node(1):
        Node* dst = new Node(2):
        Edge* edge = new Edge(src, dst);
        // add src's outgoing edge
        src->addOutEdge(edge);
        // create a graph object
        Graph* graph = new Graph();
        // add two nodes into the graph
        graph->addNode(src);
        graph->addNode(dst);
};
```

#### C++ Inheritance

Allow a child class to inherit attributes and methods from its parent class.

```
class GraphBuilder{
public:
    GraphBuilder(){}
                                              // SubGraphBuilder is a child (derived) class
                                              // of GraphBuilder
    void build(){
                                              class SubGraphBuilder : public GraphBuilder{
        cout << "parent's way to build..\n";</pre>
                                              public:
        Node* src = new Node(1):
                                                  SubGraphBuilder(){}
        Node* dst = new Node(2):
                                              }:
        Edge* edge = new Edge(src, dst);
        // add src's outgoing edge
                                              int main () {
        src->addOutEdge(edge);
                                                SubGraphBuilder* builder = new SubGraphBuilder();
        // create a graph object
                                                // reuse the build method in GraphBuilder
        Graph* graph = new Graph();
                                                builder->build():
        // add two nodes into the graph
        graph->addNode(src):
        graph->addNode(dst);
};
```

## **C++ Function Overriding**

Allow a child class to override a function (with same signature) in its parent class.

## C++ Function Overriding

Allow a child class to override a function (with same signature) in its parent class.

```
class SubGraphBuilder : public GraphBuilder{
class GraphBuilder{
                                              public:
public:
                                                  SubGraphBuilder(){}
    GraphBuilder(){}
                                                  // override `build` method in GraphBuilder
                                                  void build(){
    void build(){
                                                      cout << "child's way to build..\n";</pre>
        cout << "parent's way to build..\n";</pre>
        Node* src = new Node(1):
                                              };
        Node* dst = new Node(2);
        Edge* edge = new Edge(src, dst);
                                              int main () {
        // add src's outgoing edge
                                                SubGraphBuilder* builder1 = new SubGraphBuilder();
        src->addOutEdge(edge);
                                                // Which `huild` method will be called?
        // create a graph object
                                                builder1->build():
        Graph* graph = new Graph();
        // add two nodes into the graph
                                                GraphBuilder* builder2 = new SubGraphBuilder();
        graph->addNode(src);
                                                // Which `build` method will be called?
        graph->addNode(dst):
                                                builder2->build():
};
```

## C++ Virtual Function and Polymorphism

A function declared with a 'virtual' keyword in a parent class can be overridden by a child class. When you refer to a child class object using a pointer/reference to the parent class, it will call child class's version of this virtual function.

## C++ Virtual Function and Polymorphism

A function declared with a 'virtual' keyword in a parent class can be overridden by a child class. When you refer to a child class object using a pointer/reference to the parent class, it will call child class's version of this virtual function.

```
class SubGraphBuilder : public GraphBuilder{
class GraphBuilder{
                                              public:
public:
                                                  SubGraphBuilder(){}
    GraphBuilder(){}
                                                  void build(){ // override `build` in GraphBuilder
    virtual void build(){
                                                      cout << "child's way to build..\n";</pre>
        cout << "parent's way to build..\n":</pre>
        Node* src = new Node(1);
                                              }:
        Node* dst = new Node(2):
                                              int main () {
        Edge* edge = new Edge(src, dst);
                                                SubGraphBuilder* builder1 = new SubGraphBuilder();
        // add src's outgoing edge
                                                builder1->build(); // Which `build` will be called?
        src->addOutEdge(edge);
        // create a graph object
                                                GraphBuilder* builder2 = new SubGraphBuilder();
        Graph* graph = new Graph():
                                                builder2->build(); // Which `build` will be called?
        // add two nodes into the graph
        graph->addNode(src);
                                                GraphBuilder* builder3 = new GraphBuilder();
        graph->addNode(dst);
                                                builder3->build(): // Which `build` will be called?
```

### **Debugging Your C++ Programs**

- VSCode (https://code.visualstudio.com/docs/cpp/cpp-debug)
- GDB (https://cs.baylor.edu/~donahoo/tools/gdb/tutorial.html)
- LLDB (https://lldb.llvm.org/use/tutorial.html)
- Eclipse CDT (https://wiki.eclipse.org/CDT/StandaloneDebugger)
- Other tactics, such as printing your results
   (https://www.learncpp.com/cpp-tutorial/basic-debugging-tactics/)

### **A Quick Overview of Python**

Week 1

Yulei Sui

School of Computer Science and Engineering University of New South Wales, Australia

#### What is Python?

 Python is a high-level, interpreted general-purpose multi-paradigm programming language.

#### What is Python?

 Python is a high-level, interpreted general-purpose multi-paradigm programming language.

#### Why learn Python?

 Language for web development, data analysis, machine learning, and scripting.

#### What is Python?

 Python is a high-level, interpreted general-purpose multi-paradigm programming language.

#### Why learn Python?

- Language for web development, data analysis, machine learning, and scripting.
- User-friendly syntax which can quickly write programs and easily interface with high-performance libraries
- Provides rich library support for many applications

#### What is Python?

 Python is a high-level, interpreted general-purpose multi-paradigm programming language.

#### Why learn Python?

- Language for web development, data analysis, machine learning, and scripting.
- User-friendly syntax which can quickly write programs and easily interface with high-performance libraries
- Provides rich library support for many applications
- A popular and extensively used language

## **Python**

 This short introduction does not aim to cover every detailed aspect of Python, but rather the basic Python syntax/features in order to develop algorithms to fulfil the assignment tasks in this course.

### **Python**

- This short introduction does not aim to cover every detailed aspect of Python, but rather the basic Python syntax/features in order to develop algorithms to fulfil the assignment tasks in this course.
- You are encouraged to learn and practice more advanced Python syntax/features.
  - https://docs.python.org/3/tutorial/
  - https://www.w3schools.com/python/
  - https://cgi.cse.unsw.edu.au/~cs2041/25T1/topic/python\_intro/slides
  - Google search 'Python programming' or 'Introduction to Python programming'

### **Write Your First Python Program**

```
print("Welcome to software security analysis course!")
```

A Hello World example under Software-Security-Analysis:

https://github.com/SVF-tools/Software-Security-Analysis/blob/main/HelloWorld/hello.py

## If Statements in Python

```
x = int(input("Please enter an integer: "))
Please enter an integer: 42
if x < 0:
    \mathbf{x} = 0
    print('Negative changed to zero')
elif x == 0:
    print('Zero')
elif x == 1
    print("Single")
else:
    print('More')
```

An if statement example from the Python docs:

https://docs.python.org/3/tutorial/controlflow.html#if-statements

### For Loops in Python

```
words = ['cat', 'window', 'defenestrate']
for i in range(len(words)):
    print(words[i], len(words[i]))
```

### For Loops in Python

```
for i in range(len(words)):
    print(words[i], len(words[i]))

for w in words:
    print(w, len(w))

A for loop example from the Python docs:
https://docs.python.org/3/tutorial/controlflow.html#for-statementss
```

words = ['cat', 'window', 'defenestrate']

### **Containers/Collections**

```
#Python lists
node_ids = []
node_ids.append(1)
node_ids.append(2)
node_ids.append(2)
for i in node_ids:
    print(i)
```

### **Containers/Collections**

```
#Python lists
node_ids = []
node_ids.append(1)
node_ids.append(2)
node_ids.append(2)
for i in node_ids:
    print(i)
```

```
#Python sets
node_ids = set()
node_ids.add(1)
node_ids.add(2)
node_ids.add(2)
for i in node_ids:
    print(i)
```

### **Functions in Python**

```
def fib(n):  # write Fibonacci series less than n
    """Return a Fibonacci series less than n."""
    series = []
    a, b = 0, 1
    while a < n:
        series.append(a)
        a, b = b, a+b
print(fib(2000))</pre>
```

### **Functions in Python**

```
def fib(n): # write Fibonacci series less than n
    """Return a Fibonacci series less than n."""
    series = []
    a. b = 0.1
    while a < n:
        series.append(a)
        a, b = b, a+b
print(fib(2000))
# An alternative function definition with the typing library
from typing import List
def fib(n: int) -> List[int]:
    . . .
```

A function example from the Python docs:

 $\verb|https://docs.python.org/3/tutorial/controlflow.html#defining-functions||$ 

# **Python Classes and Objects**

- Python objects: everything in Python is an object, there are no primitive types.
- A Python class is a template for objects, and an object is an instance of a class.
- All methods are public by default, a \_ prefixed in the function name is used for protected methods or \_\_ for private methods.

# **Python Classes and Objects**

- Python objects: everything in Python is an object, there are no primitive types.
- A Python class is a template for objects, and an object is an instance of a class.
- All methods are public by default, a \_ prefixed in the function name is used for protected methods or \_\_ for private methods.

```
class Graph:
    def __init__(self, n: int, e: int):
        self.num_of_nodes: int = n
        self.num_of_edges: int = e
    def get_num_of_nodes(self) -> int:
        return self.num_of_nodes
    def set_num_of_nodes(self, n: int):
        return self.nodes
    def get_paths(self) -> Set[str]:
        return self.paths
```

# **Python Classes and Objects**

- Python objects: everything in Python is an object, there are no primitive types.
- A Python class is a template for objects, and an object is an instance of a class.
- All methods are public by default, a \_ prefixed in the function name is used for protected methods or \_\_ for private methods.

```
class Graph:
    def __init__(self, n: int, e: int):
        self.num_of_nodes: int = n
        self.num_of_edges: int = e

    def get_num_of_nodes(self) -> int:
        return self.num_of_nodes
    def set_num_of_nodes(self, n: int):
        return self.nodes

    def get_paths(self) -> Set[str]:
        return self.paths
```

## **Building a Graph with more Functionality**

```
class Node:
   def __init__(self, i: int):
        self.node id = i
        self.out_edges = set()
    def get_node_id(self) -> int:
        return self.node id
    def get_out_edges(self) -> Set[Edge]:
        return self.out_edges
class Edge:
    def __init__(self, s: Node, d: Node):
        self.src = s
        self.dst = d
    def get_src(self) -> Node:
        return self.src
    def get_dst(self) -> Node:
       return self.dst
```

## **Building a Graph with more Functionality**

```
class Node:
    def __init__(self, i: int):
        self.node id = i
        self.out_edges = set()
    def get_node_id(self) -> int:
        return self node id
    def get_out_edges(self) -> Set[Edge]:
        return self.out_edges
class Edge:
    def __init__(self, s: Node, d: Node):
        self src = s
        self.dst = d
    def get_src(self) -> Node:
        return self.src
    def get_dst(self) -> Node:
        return self.dst
```

```
class Graph:
   def init (self):
        self.nodes: Set[Node] = set()
   def get_nodes(self) -> Set[Node]:
       return self.nodes
src = Node(1)
dst = Node(2)
edge = Edge(src, dst)
# add src's outgoing edge
src.get_out_edges().add(edge)
# create a graph object
graph = Graph()
# add two nodes into the graph
graph.get_nodes().add(src)
graph.get_nodes().add(dst)
```

## **Debugging Your Python Programs**

- VSCode (https://code.visualstudio.com/docs/python/debugging)
- PDB (https://docs.python.org/3/library/pdb.html)
- Other tactics, such as printing your results (https://adamj.eu/tech/2021/10/08/tips-for-debugging-with-print/)